

MAS POWER

Marine Diesel Gensets

8-10 kW



Standard Features

- EPA Certified
- Stainless Steel Drip Pan
- Stainless Mounting Supports with Rubber Isolators
- Freshwater Cooling / Heat Exchanger
- Water Cooled Stainless Steel Exhaust Elbow
- Fuel Lines Plumbed to Stainless Connection Block
- Oil Change Hose Plumbed through Pan
- 12V Electric Fuel Pump with push button primer switch
- Convenient Single Side Serviceability
- Safety Shutdowns
 - Low Oil Pressure
 - High Coolant Temperature
 - High Exhaust Temperature
- Frequency / Voltage Regulation
- Overcranking

Standard Controls

- Circuit Breaker
- Digital Genset Controller

Optional Equipment

- Plug-In Extension Wiring Harnesses (10', 20', 30', 50')
- Remote Instrument Panel
 - Remote Start / Stop Panel
 - Four Gauge Panel
 - Oil Pressure
 - Coolant Temperature
 - A/C Volts
 - A/C Amps
- Auto Start
- Siphon Break
- 50Hz Units Available

Specifications		
MODEL	MP8ML	MP11ML
kW @ 60Hz	8 (7.5 continuous)	10 (11 continuous)
kW @ 50Hz	6 (5.5 continuous)	7.5 (7 continuous)
Engine (Kohler)	LDW1003	LDW1404
Aspiration	Natural	
CID (CC)	62.7 (1028)	83.7 (1372)
Dimensions		
L inches (mm)	31 (787.4)	40 (1016)
W inches (mm)	22 (558.8)	
H inches (mm)	21.5 (546.1)	
Dimensions with Sound Enclosure		
L inches (mm)	34 (863.6)	44 (1117.6)
W inches (mm)	22.75 (577.85)	
H inches (mm)	23.5 (596.9)	
Weight(wet) lbs (kg)	540 (244.9)	610 (276.6)
Speed		
RPM (60Hz)	1800	
RPM (50Hz)	1500	
No. of Cylinders	3	4
Horsepower		
1800 RPM	14.5	19.6
1500 RPM	11.9	15.4
Battery Voltage	12V	
Fuel Consumption (GPH)		
100% Load	.9	1.2
75% Load	.7	.9
Amperage (1 Phase)		
120/240V	75/37.5	92/46
Voltage Regulation	Electronic	
Voltage Regulation	+3%	
Frequency Regulation	+4%	



www.maspowerproducts.com
 2801 Anvil Street N • St. Petersburg, Florida 33710
 Tel. 727.522.9471 • Fax 727.527.7013
 Toll Free 800.545.4574